

SCA 200

Automatic lathe positioner 200Kg load capacity

Positioner for the simultaneous automatic orbital welding of circular pieces, maximum load 200 kg. Rotation activated by a direct current electrical motor, speed electronically adjusted by current feedback. Bimanual control driven tail-stock. Customizable bench length.

The working length between the tail-stock and the table can be customized on request.



HF shielding included in all the models

SCA 1200	Automatic rotary table, 1 pneumatic gun supporting arm - Max. working length: mm. 1200	
SCA 2000	Automatic rotary table, 1 pneumatic gun supporting arm - Max. working length: mm. 2000	
SCA 3000	Automatic rotary table, 1 pneumatic gun supporting arm - Max. working length: mm. 3000	
SCA 4000	Automatic rotary table, 1 pneumatic gun supporting arm - Max. working length: mm. 4000	

Packaging 2%

Options

BA	Second pneumatic gun support and dual welding control	
GAS	Tail stock with gas injection (BAC- BACB models)	
SMDS 60	Modular skid for gun supporting arm, stroke: 60 mm	
SMDT 60	Modular skid for fold-gun supporting arm, stroke: 60 mm	
V-SUP200	V-supports manually adjustable	
CONSOLLE	External consolle with control panel	
Ø 800	Optional working diameter up to Ø800mm + External consolle with control panel	